



Part Description

UBS' standard product line of short length high power terminations are constructed similar to the medium power terminations.

Ordering Data

Part number - 136 - X - X - X



Flange Configuration

Flange Type	C - Cover G - Groove CHOKE CMR CPR(F, G)
Flange Mounting Holes	T1 - Through Holes T2 - Threaded A - Alternating

Electrical Specification

VSWR	< 1.10 max.
-------------	-------------

STANDARD FINISH: is electroless corrosion protection for the metal surface. Non standard configurations and finishes (Silver, Nickel, Cadmium plating) are available upon request. Waveguide sizes up to WR-650 available. Contact our sales department with your requirements.

Notes

1. All dimensions are for reference only
2. Depending on waveguide size and power requirements, the termination may require a heatsink. If required, UBS will advise and quote the termination with the heatsink included
3. All heatsinks selected based on natural convection cooling. For Forced air cooling, contact factory

Specifications

Size	Frequency GHz	Dimensions (inches)			Average Power Watts
		A	B	C	
WR28	26.50 - 40.00	5.00	2.30	3.40	50
WR34	22.00 - 33.00	5.00	2.30	3.40	75
WR42	18.00 - 26.00	5.00	2.30	3.40	150
WR51	15.00 - 22.00	5.00	2.30	3.40	110
WR62	12.40 - 18.00	5.00	2.30	3.40	200
WR75	10.00 - 15.00	8.00	5.20	5.15	200
WR90	8.20 - 12.40	8.00	5.20	5.15	225
WR112	7.05 - 10.00	8.00	5.20	5.15	425
WR137	5.85 - 8.20	8.00	5.20	5.15	500
WR159	4.09 - 7.05	9.00	5.20	5.15	625
WR187	3.95 - 5.85	9.50	5.20	5.15	750
WR229	3.30 - 4.90	12.00	5.20	5.15	1000
WR284	2.60 - 3.95	13.00	5.20	5.15	1200
WR340	2.20 - 3.30	-	-	-	-
WR430	1.70 - 2.60	-	-	-	-

(specifications are subject to change without notice)